

2016 Mudd-Ox Fort Mac Fully Hydraulic 8x8 with 20" Chevron Tracks

Engine

Type	Gasoline
Model	Ford MSG-425 EFI
Power Output	85 HP at 3,000 rpm
Displacement	2.5 Liter (152.5 CID)
Cooling	Liquid-Cooled
Starting	Electric Starter
Electrical	Maxx N65 Battery, 130 Amp Alternator

Transmission

Transmission	Fully Hydrostatic with Low and High Range
--------------	---

Controls & Instrumentation

Steering	Ergonomic Left and Right Steering Controls
Parking Brake	Spring Applied Hydraulic Released
Instrumentation	Full Instrumentation Dash Panel
Gauges	Tachometer Fuel Gauge Volt Meter Hour Meter Coolant Temperature Hydraulic Temperature
Warning Lights	Low Oil Pressure Parking/Emergency Brake Neutral Light Check Engine

Chassis, Body & Lights

Frame	Powder coated steel for long life and durability
Body	Vacuum formed upper body, lower body and skid plate, made from High Molecular Weight Polyethylene (HMWPE)
Tires	26" x 14" x 12" Mudd-Ox Vendetta on 12" Mudd-Ox Bead Lock Rim
Lighting	Halogen Headlights with LED Tail Lights

Performance

Speed - Land	Low Range 15 mph [A] (24 km/h) High Range 25 mph [A] (40 km/h)
Speed - Water	3 mph (5 km/h) [B]
Load Capacity - Land	2,000 lbs. (907 kg)(distributed evenly) Less the weight of any accessories [C]
Load Capacity - Water	1,000 lbs. (454 kg)(distributed evenly) Less the weight of any accessories [C]
Turning Circle	Zero turning radius, Tracks counter-rotate
Towing Capacity	2,000 lbs. (907 kg)
Seating Capacity - Land	4 to 6 [D]
Seating Capacity - Water	2 to 4 [D]

Available Colors



Mudd-Ox

8525 W. 750 N.
Shipshewana, IN 46565
Phone: 260-768-7221
Fax: 260-768-3074
Web: www.muddox.net
E-mail: info@muddox.net

Safety

Safety	Fold down Roll Over Protection System with seat belts for front two passengers. Rear Roll Over Protection System is available as an option. Mudd-Ox Hydrostatic precision control drive system enables safe control at all times while maneuvering in the most difficult terrains.
Fuel Capacity	12 US gallons, giving approximately 8 hours of operation.
Operating Conditions	All weather, all terrain, -40°F to +110°F (-40°C to +43°C)

Ground Clearance

Ground Clearance	14" at center of vehicle
Ground Pressure	2 psi

Operation & Convenience

Self-Extraction Winch	5,000 lb. Capacity
Storage	Lockable glove box, Built in Cup Holders and 12.5" x 28" Insert area over engine cover
Electrical Output	12V Outlet, USB Port
Bilge Pump	Standard

Weight & Dimensions

Weight	3,000 lbs. on 20" Chevron Tracks
Dimensions	123" Long x 64" Wide x 78" High with Roll Bar Up, 62" High with Roll Bar Down. Machine is 81" Wide on Tracks.
Approach and Departure angles	25° Maximum

Warranty

Warranty	1 year limited warranty on Mudd-Ox, 2 year engine warranty [E]
----------	--

Specifications are subject to change without notice.

- [A] Top speed depends on terrain conditions and drive train options.
[B] Depends on water conditions, only operate in calm water without a current (No large lakes, open waters, oceans.)
[C] See Owner's manual for accessory listing and weight.
[D] Depending on weight of person, cargo and accessories onboard
[E] See Owner's Manual for full warranty information.
[F] Provides better flotation and allows for more carrying capacity in the water.

Accessories

- Aluminum Cab
- Air Conditioning
- Cab Heater
- Brush Guard
- Canvas Half Cab
- Snow Plow
- Rear Roll Bar
- Amphibious Trailer
- Float Kit [F]
- Windshield
- Marine Stereo
- 9.9 Four Stroke Outboard Motor
- Outboard Motor Mount Kit
- Rear Cargo Liner
- Rear Winch Kit
- Windshield Wiper Kit
- Rear Fuel Fill

Full Range of Accessories - See www.muddox.net